



Material (材料)>>>

Plastic material (塑胶材质) : PA6T/PA9T+30%G.F
Color (颜色) : Black、Special
Insulator Material (绝缘材料) : Polyester(UL94V-0)
Contact Material (接触材料) : Brass
Contact Plating (接触电镀) : Au Or Sn over 40u" Ni



010-01



SPECIFICATIONS (规范)>>>

Current Rating (额定电流) : 0.75Amps
Withstanding Voltage (耐电压) : AC 500Vmin/Minute
Insulation Resistance (绝缘电阻) : 1000MΩ Min
Contact Resistance (接触电阻) : 20 mΩ MAX
Operation Temperature (工作温度) : -40°Cto+105°C

010-02



Material code(物料编码)>>>

P	100	2XX	M	B	A	XX	001
品名	间距	Pin位	类型	材质	包装方式	电镀	尺寸
Type P=Pin Header	Pitch 100=1.00	No.of Rows 2x01-50Pin	Connector Type M=SMT	Insulator Material Option B=BK-PA6T C=BK-PA9T D=LCP S=Special	packing A=Bag B=Box C=Tube D=Tape Reel	Contact Plating S:Ni G2:1U"Gold G3:3U"Gold G4:5U"Gold G5:10U"Gold G6:15U"Gold Standard:G0	Size HWWL/PA/PB/PD/PW

1.0mm Pin Header