



**Material (材料)>>>**

Plastic material (塑胶材质) : PBT/PA6T/PA9T/LCP+30%G.F  
Color (颜色): Black, White, blue  
Insulator Material (绝缘材料): Polyester(UL94V-0)  
Contact Material (接触材料) : Brass  
Contact Plating (接触电镀): Au Or Sn over 40u" Ni



**SPECIFICATIONS (规范)>>>**

Current Rating (额定电流): 3.0 Amps  
Withstanding Voltage (耐电压) : AC 1000Vmin/Minute  
Insulation Resistance(绝缘电阻): 1000MΩ Min  
Contact Resistance (接触电阻): 20 mΩ MAX  
Operation Temperature(工作温度): -40°Cto+105°C

053-01



053-02



**Material code(物料编码)>>>**

<b>P</b>	<b>254</b>	<b>XXX</b>	<b>U</b>	<b>B</b>	<b>C</b>	<b>G0</b>	<b>001</b>
品名 Type P=Pin Header	间距 Pitch 2.54=254	Pin位 No. of Rows 1x01-40Pin	类型 Connector Type U=U-Type	材质 Insulator Material Option A=BK-PBT B=BK-PA6T C=BK-PA9T D=LCP S=Special	包装方式 packing A=Bag B=Box C=Tube D=Tape Reel	电镀 Contact Plating SN:Tim G0:Gold Flash G2:1U*Gold G3:3U*Gold G4:5U*Gold G5:10U*Gold G6:15U*Gold Standard:G0	尺寸 Size H/L/PC/PW/PD

2.54mm Pin Header