




Material (材料)>>>

Plastic material (塑胶材质) : PA9T/LCP+30%G.F
Color (颜色): Black
Insulator Material (绝缘材料) : Polyester(UL94V-0)
Contact Material (接触材料) : Brass
Contact Plating (接触电镀) : Au Or Sn over 40u" Ni




054-01



SPECIFICATIONS (规范)>>>

Current Rating(额定电流) : 7.0 Amps
Withstanding Voltage(耐电压) : AC 500Vmin/Minute
Insulation Resistance(绝缘电阻) : 1000M Ω Min
Contact Resistance (接触电阻) : 20 m Ω MAX
Operation Temperature(工作温度) : -40°C to $+105^{\circ}\text{C}$

054-02



Material code(物料编码)>>>

P	396	1XX	S	A	A	SN	001
品名	间距	Pin位	类型	材质	包装方式	电镀	尺寸
Type P=Pin Header	Pitch 3.96=396	No.of Rows 1x01-20Pin	Connector Type S=Straight	Insulator Material Option C=BK-PA9T D=LCP S=Special	packing A=Bag B=Box C=Tube D=Tape Reel	Contact Plating SN: Tin G0: Gold Flash G2: 1U" Gold G3: 3U" Gold G4: 5U" Gold G5: 10U" Gold G6: 15U" Gold Standard: G0	Size H/L/PA/PC/PD

3.96mm Pin Header