

Product Picture	Part Number	Data Rate	Ports	Packaged Type	VT (V(RMS))	Operating Temperature	PoE	DC Line Current (mA)	L(uH)	MPQ (PCS)	Size (mm)	Remark
	TF-1016DG	10/100M	1	DIP12	1500	0-70	N/A		350	40	12.75*7.30*6.60	
	TF-1601DG	10/100M	1	DIP16	1500	0-70	N/A		350	25	20.40*10.16*6.75	
	TF-1605DG	10/100M	1	DIP16	1500	0-70	N/A		350	25	20.30*10.00*6.80	
	TF-1606DG	10/100M	1	DIP16	1500	0-70	N/A		350	25	20.40*10.16*6.75	
	TF-208DG	10/100M	2	DIP20	1500	0-70	N/A		350	20	25.50*10.00*6.90	
	TF-218DG	10/100M	2	DIP20	1500	0-70	N/A		350	24	21.20*9.80*8.10	
	B1201D	10/100M	1	DIP12	1500	0-70	N/A		350	40	12.75*7.30*6.60	
	B1202D	10/100M	1	DIP12	1500	0-70	N/A		350	40	12.75*7.30*6.60	
	B1203D	10/100M	1	DIP12	1500	0-70	N/A		350	40	12.75*7.30*6.60	
	B1601S	10/100M	1	SMD16	1500	0-70	N/A		350	600	12.70*7.00*5.70	
	B1602S	10/100M	1	SMD16	1500	0-70	N/A		350	600	12.70*7.00*5.70	
	B1603S	10/100M	1	SMD16	1500	0-70	N/A		350	2000	12.70*7.10*2.25	
	B1604S	10/100M	1	SMD16	1500	0-70	N/A		350	600	12.70*7.00*5.70	
	B1605S	10/100M	1	SMD16	1500	-40-85	PoE+	720	350	600	12.70*7.00*5.70	
	B1608S	10/100M	1	SMD16	1500	-40-85	PoE+	720	350	600	12.70*7.00*5.70	

[illegible]

Product Picture	Part Number	Data Rate	Ports	Packaged Type	VT (V(RMS))	Operating Temperature	PoE	DC Line Current (mA)	L(uH)	MPQ (PCS)	Size (mm)	Remark
	G1801D	100/1000M	1	DIP18	1500	0-70	N/A		350	30	16.80*8.50*11.50	
	G1802D	100/1000M	1	DIP18	1500	0-70	N/A		350	30	16.80*8.50*11.50	
	G1803D	100/1000M	1	DIP18	1500	0-70	N/A		350	30	16.80*8.50*11.50	
	G1804D	100/1000M	1	DIP18	1500	0-70	N/A		350	30	16.80*8.50*11.50	
	G2015D	100/1000M	1	DIP20	1500	0-70	N/A		350	24	21.00*12.50*6.90	
	G2401D	100/1000M	1	DIP24	1500	0-70	N/A		350	32	15.50*11.00*11.00	
	G2401S	100/1000M	1	SMD24	1500	0-70	N/A		350	420	17.80*12.25*6.00	
	G2402S	100/1000M	1	SMD24	1500	0-70	N/A		350	420	17.80*12.25*6.00	
	G2403S	100/1000M	1	SMD24	1500	0-70	N/A		350	1100	13.97*9.70*2.30	
	G2406S	100/1000M	1	SMD24	1500	0-70	N/A		350	850	15.10*7.10*4.00	
	G24121S	100/1000M	1	SMD24	1500	-40-85	PoE+	720	350	420	17.80*12.25*6.00	
	G24123S	100/1000M	1	SMD24	1500	-40-85	PoE+	1100	350	420	17.80*12.25*6.00	
	G2412S	100/1000M	1	SMD24	1500	-40-85	PoE	350	350	420	17.80*12.25*6.00	
	G2413S	100/1000M	1	SMD24	1500	0-70	N/A		350	400	13.06*12.50*3.05	
	G2415S	100/1000M	1	SMD24	1500	-40-85	N/A		350	850	15.10*7.10*4.00	

Product Picture	Part Number	Data Rate	Ports	Packaged Type	VT (V(RMS))	Operating Temperature	PoE	DC Line Current (mA)	L(uH)	MPQ (PCS)	Size (mm)	Remark
	G2419S	100/1000M	1	SMD24	1500	-40-85	PoE+	720	350	850	15.10*7.10*4.00	
	G2423S	100/1000M	1	SMD24	1500	-40-85	PoE+	720	350	420	17.80*12.25*6.00	
	G2425S	100/1000M	1	SMD24	1500	0-70	N/A		350	1100	15.60*8.50*2.30	
	G24251S	100/1000M	1	SMD24	1500	-40-85	N/A		350	1100	15.60*8.50*2.30	
	G2426S	100/1000M	1	SMD24	1500	0-70	N/A		350	1100	15.60*8.50*2.30	
	G24261S	100/1000M	1	SMD24	1500	-40-85	N/A		350	1100	15.60*8.50*2.30	
	G2436S	100/1000M	1	SMD24	1500	-40-85	PoE	550	350	850	15.10*7.10*4.00	
	G2437S	100/1000M	1	SMD24	1500	0-70	N/A		350	1000	19.80*16.60*2.54	
	G3601D	100/1000M	2	DIP36	1500	0-70	N/A		350	15	32.50*8.30*11.75	
	G3604D	100/1000M	2	DIP36	1500	0-70	N/A		350	15	32.50*8.30*11.75	
	G4801D	100/1000M	2	DIP48	1500	0-70	N/A		350	18	28.00*11.00*11.00	
	G4801S	100/1000M	2	SMD48	1500	0-70	N/A		350	300	27.80*12.25*7.0	
	G4802D	100/1000M	2	DIP48	1500	0-70	N/A		350	18	28.00*11.00*11.00	
	G4803D	100/1000M	2	DIP48	1500	0-70	N/A		350	18	28.00*11.00*11.00	
	G4812S	100/1000M	2	SMD48	1500	-40-85	PoE+	720	350	300	27.80*12.25*7.0	

Product Picture	Part Number	Data Rate	Ports	Packaged Type	VT (V(RMS))	Operating Temperature	PoE	DC Line Current (mA)	L(uH)	MPQ (PCS)	Size (mm)	Remark
	G4814S	100/1000M	2	SMD48	1500	-40-85	PoE	550	350	300	27.80*12.25*7.0	
	G4815S	100/1000M	2	SMD48	1500	-40-85	PoE+	720	350	300	27.80*12.25*7.0	
	G4818S	100/1000M	2	SMD48	1500	-40-85	N/A		350	300	27.80*12.25*7.0	
	G4841S	100/1000M	2	SMD48	1500	-40-85	PoE+	720	350	300	27.80*12.25*7.0	
	G5001S	100/1000M	2	SMD50	1500	0-70	N/A		350	450	27.80*7.30*8.30	
	G5002S	100/1000M	2	SMD50	1500	0-70	N/A		350	450	27.80*7.30*8.30	
	G5004S	100/1000M	2	SMD50	1500	0-70	N/A		350	450	27.80*7.30*8.30	
	G5005S	100/1000M	2	SMD50	1500	0-70	N/A		350	450	27.80*7.30*8.30	
	G5007S	100/1000M	2	SMD50	1500	-40-85	PoE+	720	350	450	27.80*7.30*8.30	
	G5010S	100/1000M	2	SMD50	1500	-40-85	N/A		350	450	27.80*7.30*8.30	
	G7202D	100/1000M	4	DIP72	1500	0-70	N/A		350	12	34.50*19.00*13.00	
	G8801D	100/1000M	4	DIP88	1500	0-70	N/A		350	14	26.50*29.00*13.00	
	G8805D	100/1000M	4	DIP88	1500	0-70	N/A		350	14	26.50*29.00*13.00	
	G9601D	100/1000M	4	DIP96	1500	0-70	PoE+	720	350	14	28.50*27.80*17.00	
	G9602D	100/1000M	4	DIP96	1500	-40-85	N/A		350	14	28.50*27.80*17.00	

Product Picture	Part Number	Data Rate	Ports	Packaged Type	VT (V(RMS))	Operating Temperature	PoE	DC Line Current (mA)	L(uH)	MPQ (PCS)	Size (mm)	Remark
	QG2401D	2.5G	1	DIP24	1500	-40-85	N/A		180	32	15.50*11.00*11.35	
	QG2402D	2.5G	1	DIP24	1500	-40-85	N/A		180	32	15.50*11.00*11.35	
	QG2432S	2.5G	1	SMD24	1500	-40-85	N/A		180	400	13.51*12.20*6.09	
	QG2433S	2.5G	1	SMD24	1500	-40-85	N/A		180	400	13.51*12.20*6.09	
	QG2434S	2.5G	1	SMD24	1500	-40-85	N/A		180	1100	16.50*9.70*2.30	
	QG2435S	2.5G	1	SMD24	1500	-40-85	PoE	600	180	850	15.10*7.10*4.00	
	QG2437S	2.5G	1	SMD24	1500	-40-85	N/A		180	850	15.10*7.10*4.00	
	QG2438S	2.5G	1	SMD24	1500	-40-85	PoE	600	180	400	17.55*12.25*6.00	
	QG24381S	2.5G	1	SMD24	1500	-40-85	PoE+	720	180	400	17.55*12.25*6.00	
	QG24382S	2.5G	1	SMD24	1500	-40-85	PoE+	1100	180	400	17.55*12.25*6.00	
	QG24383S	2.5G	1	SMD24	1500	-40-85	PoE+	1100	180	400	17.55*12.25*6.00	
	QG2439S	2.5G	1	SMD24	1500	-40-85	N/A		180	850	15.10*7.10*4.00	
	QG2442S	2.5G	1	SMD24	1500	-40-85	N/A		180	850	15.10*7.10*4.00	
	QG2443S	2.5G	1	SMD24	1500	-40-85	PoE+	720	180	400	17.55*12.25*6.00	
	QG24433S	2.5G	1	SMD24	1500	-40-85	PoE+	1100	180	400	17.55*12.25*6.00	

Product Picture	Part Number	Data Rate	Ports	Packaged Type	VT (V(RMS))	Operating Temperature	PoE	DC Line Current (mA)	L(uH)	MPQ (PCS)	Size (mm)	Remark
	QG4850S	2.5G	2	SMD48	1500	-40-85	N/A		180	300	27.80*12.20*7.25	
	QG4851S	2.5G	2	SMD48	1500	-40-85	PoE+	720	180	300	27.80*12.20*7.25	
	QG4852S	2.5G	2	SMD48	1500	-40-85	PoE+	1100	180	300	27.80*12.20*7.25	
	QG4855D	2.5G	2	DIP48	1500	-40-85	N/A		180	18	28.10*11.10*12.00	
	QG4856D	2.5G	2	DIP48	1500	-40-85	N/A		180	18	28.10*11.10*12.00	
	QG5010S	2.5G/5G	2	SMD50	1500	-40-85	N/A		180	450	27.80*7.30*8.30	
	FG2431S	5G	1	SMD24	1500	-40-85	N/A		150	1100	16.50*9.70*2.30	
	FG2440S	5G	1	SMD24	1500	-40-85	N/A		150	400	17.55*12.25*6.00	
	FG2441S	5G	1	SMD24	1500	-40-85	N/A		150	400	17.55*12.25*6.00	
	FG2447S	5G	1	SMD24	1500	-40-85	PoE+	720	150	400	17.55*12.25*6.00	
	FG2460S	5G	1	SMD24	1500	-40-85	N/A		150	850	15.10*7.10*4.00	
	FG4852D	5G	1	DIP48	1500	-40-85	PoE+	720	150	18	28.10*11.10*12.00	
	FG4860S	10G	2	SMD48	1500	-40-85	N/A		150	300	27.80*12.20*7.50	
	TG2401D	10G	1	DIP24	1500	-40-85	N/A		120	32	15.50*10.90*12.00	
	TG2480S	10G	1	SMD24	1500	-40-85	N/A		120	32	15.50*10.90*12.00	

Product Picture	Part Number	Data Rate	Ports	Packaged Type	VT (V(RMS))	Operating Temperature	PoE	DC Line Current (mA)	L(uH)	MPQ (PCS)	Size (mm)	Remark
	TG2481S	10G	1	SMD24	1500	-40-85	N/A		120	400	13.51*12.20*6.09	
	TG2482S	10G	1	SMD24	1500	-40-85	PoE+	720	100	400	13.51*12.20*6.09	
	TG2483S	10G	1	SMD24	1500	-40-85	N/A		120	850	15.10*7.10*4.00	
	TG2484S	10G	1	SMD24	1500	-40-85	N/A		120	400	17.60*12.20*6.00	
	TG2485S	10G	1	SMD24	2250	-40-85	N/A		100	400	17.55*12.25*6.00	
	TG2486S	10G	1	SMD24	1500	-40-85	N/A		120	1100	16.50*9.70*2.30	
	TG2487S	10G	1	SMD24	1500	-40-85	N/A		120	850	15.10*7.10*4.00	
	TG2488S	10G	1	SMD24	1500	-40-85	PoE+	720	120	400	17.55*12.25*6.00	
	TG24883S	10G	1	SMD24	1500	-40-85	PoE+	1100	120	400	17.55*12.25*6.00	
	TG2491S	10G	1	SMD24	1500	-40-85	N/A		160	400	13.51*12.20*6.09	
	TG2494S	10G	1	SMD24	1500	-40-85	PoE+	720	160	400	18.00*12.25*6.35	
	TG2495S	10G	1	SMD24	1500	-40-85	PoE+	720	120	400	17.55*12.25*6.00	
	TG2497S	10G	1	SMD24	1500	-40-85	PoE+	1100	120	400	17.55*12.25*6.00	
	TG2498S	10G	1	SMD24	1500	-40-85	PoE+	1100	120	400	17.55*12.25*6.00	
	TG3058S	10G	1	SMD30	1500	-40-85	PoE+	720	120	300	17.75*12.00*6.00	

[illegible]