



备注:

1.材质:

- 1.1胶芯: LCP+30%G.F UL94V-0
- 1.2端子: C18140, T=0.12mm; 镍底, 镀金Xμ”
- 1.3外壳: 不锈钢, T=0.30mm; 表面镀镍100μ”或亮锡100μ”

2.主要特性:

- 2.1额定电流: 3A
- 2.2接触阻抗: 40mΩ MAX
- 2.3绝缘阻抗: 100MΩ MIN 250V DC
- 2.4耐压测试: 100V AC
- 2.5沾锡性: 温度250iA5℃, 时间5iA0.5s
- 2.6整体插入力: 2.0kgf MAX
整体拔出力: 0.6kgf MIN
- 2.7使用寿命: 5000次
- 2.8工作温度: -30℃~+80℃

振端精密科技 (深圳) 有限公司
Zhenduan precision technology (Shenzhen) Co., Ltd

TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.X ±0.05 X.X ±0.02 X.X ±0.01	DRAWN BY :	DATE :	PART NAME:	
	刘志强	2015.08.18	TYPE-C16P四脚贴板H7.35	
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY :	DATE :	PART NO.	SEE TABLE
	李毅	2015.08.18	MOLD NO.	
	APPROVED BY :	DATE :	DRAW NO.:	ZDJNKJ00001626
	张少辉	2015.08.18	SHEET NO.	1 OF 1