

备注

1. 产品规格:


- 1-1. 插入力: 35N MAX.
- 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER 1500 CYCLES
- 1-3. 额定电流: 1.0A
- 1-4. 额定电压: 30V
- 1-5. 耐久性: 1500 CYCLES MIN.
- 1-6. 耐电压: 100V AC MIN.
- 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER 1500 CYCLES
- 1-8. 绝缘电阻: 100MΩ MIN
- 1-9. 工作温度: -30\*TO +80\*

2. 材质:

- 2.1 胶芯: LCP UL94V-0
- 2.2 端子: C2680R-H, 镍底, GOLD
- 2.3 外壳: SPCCorSUS, 表面镀镍60-100μ

3. 所用材质须符合RoHS要求

4. 重点尺寸标识"▲"符号



尺寸	允许公差
X.	±0.50
.X	±0.20
.XX	±0.10
.XXX	±0.03
角度	±1.00°



振端精密科技(深圳)有限公司  
Zhenduan precision technology (Shenzhen) Co., Ltd

TOLERANCE:	±0.30
XXX	±0.20
.XXX	±0.10
.XX	±0.10
.X	±0.20
X	±0.50
UNIT: mm [inch]	
SCALE: 1:1	SIZE: A4

DRAWN BY:	DATE:	PART NAME:
刘志强	2015.08.18	MC2P母座立式插板1H14.0无柱
CHECKED BY:	DATE:	PART NO.
李毅	2015.08.18	SEE TABLE
APPROVED BY:	DATE:	MOLD NO.
张少辉	2015.08.18	
		DRAW NO:
		ZDJNKM000101
		SHEET NO.
		1 OF 1