



规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
2. 端子: Contact: Copper Alloy C1591
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Talls
端子四周镀50U”(MIN)锡, 镀全区域镀100-200U”镀金1U”
2. 外壳: Shell:
铁壳四周镀80U”(MIN)锡

振端精密科技 (深圳) 有限公司
Zhenduan precision technology (Shenzhen) Co., Ltd

| | | | | |
|--|-------------|------------|----------------|----------------|
| TOLERANCE: X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.XX ±0.10 X.X ±0.05 X.X ±0.05 | DRAWN BY : | DATE : | PART NAME: | |
| | 刘志强 | 2015.08.18 | MC2P母座90插板加长直边 | |
| UNIT: mm [inch] SCALE: 1:1 SIZE: A4 | CHECKED BY: | DATE : | PART NO. | SEE TABLE |
| | 李毅 | 2015.08.18 | MOLD NO. | |
| APPROVED BY: | | DATE : | DRAW NO.: | ZDJNKJMC000102 |
| 张少辉 | | 2015.08.18 | SHEET NO. | 1 OF 1 |