



- Material:
  - Contact: Phosphor Bronze
  - Insulator: PBT+30%
  - G.F. UL 94V-0
  - Shell: SPCC
- Mechanical:
  - Mating: 35N max.
  - Withdrawal Force: 10N min.
  - Durability: 1500 cycles min.
- Electrical:
  - Current-max (amps) 1.0A
  - Voltage-max (volts) 30V
  - Withstanding Voltage 750V AC
  - Contact Resistance (ohms) 30 milliohms max
  - Insulation Resistance (ohms) 1000 Megohms min.
- Plating:
  - Contacts: Gold and Tin Over Nickel Plated
  - Shell: Nickel over all plating.
- Environmental:
  - Temperature Range: -55 to 85

<b>振端精密科技 (深圳) 有限公司</b> Zhenduan precision technology (Shenzhen) Co., Ltd			
TOLERANCE: XXX $\pm 0.30$ X:XXX $\pm 0.20$ X:XXX $\pm 0.10$ X:XXX $\pm 0.05$ X:XXX $\pm 0.02$	DRAWN BY: 刘志强 DATE: 2015.08.18	PART NAME: MC2P母座90插板卷边	
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY: 李毅 DATE: 2015.08.18	PART NO. SEE TABLE MOLD NO.	DRAW NO: ZDJNKJMC000103 SHEET NO. 1 OF 1
	APPROVED BY: 张少辉 DATE: 2015.08.18		