



备注:

1. 产品规格:

- 1-1. 插入力: 35N MAX.
- 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER
- 1-3. 额定电流: 1.0A
- 1-4. 额定电压: 30V
- 1-5. 耐久性: 10000 CYCLES MIN.
- 1-6. 耐电压: 100V AC MIN.
- 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER
- 1-8. 绝缘电阻: 100MΩ MIN
- 1-9. 工作温度: -30° TO +80°

2. 材质:

- 2.1 胶芯: LCP UL94V-0
- 2.2 端子: C2680R-H, 镍底, 镀金 1μ"
- 2.3 外壳: SUS201/301, 表面镀雾锡/镀镍

3. 重点尺寸标识"▲"符号

| | | | |
|---|--------------------------|--------------------------------------|---------------------------------------|
| 振端精密科技 (深圳) 有限公司 Zhenduan precision technology (Shenzhen) Co., Ltd | | | |
| TOLERANCE: X.XX ±0.30 X.XX ±0.20 X.XXX ±0.10 X.X ±0.05 X.X ±0.02 | DRAWN BY : 刘志强 | DATE : 2015.08.18 | PART NAME: MC5P母座立插贴板卷边 |
| UNIT: mm [inch] SCALE: 1:1 SIZE: A4 | CHECKED BY: 李毅 | DATE : 2015.08.18 | PART NO. SEE TABLE MOLD NO. |
| APPROVED BY: 张少辉 | DATE : 2015.08.18 | DRAW NO.: ZD.JNK.JMC000118 | SHEET NO.: 1 OF 1 |