



- 备注:
- 产品规格:
 - 1-1. 插入力: 35N MAX.
 - 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER
 - 1-3. 额定电流: 1.0A
 - 1-4. 额定电压: 30V
 - 1-5. 耐久性: 10000 CYCLES MIN.
 - 1-6. 耐电压: 100V AC MIN.
 - 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER
 - 1-8. 绝缘电阻: 100MΩ MIN
 - 1-9. 工作温度: -30° TO +80°
 - 材质:
 - 2.1 胶芯: LCP UL94V-0
 - 2.2 端子: C2680R-H, 镍底, 镀金 1μ "
 - 2.3 外壳: SUS201/301, 表面镀雾锡/镀镍
 - 重点尺寸标识"▲"符号

振端精密科技 (深圳) 有限公司 Zhenduan precision technology (Shenzhen) Co., Ltd			
TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.X ±0.10 X.X ±0.05 X.X ±0.02	DRAWN BY : 刘志强 CHECKED BY : 李毅 APPROVED BY : 张少辉	DATE : 2015.08.18 DATE : 2015.08.18 DATE : 2015.08.18	PART NAME: MC5P母座四脚贴沉板1.2卷边 PART NO. SEE TABLE MOLD NO. / DRAW NO. ZDJNKMJC000129 SHEET NO. 1 OF 1
UNIT: mm [inch] SCALE: 1:1 SIZE: A4			