

备注:

1. 产品规格:

1-1. 插入力: 35N MAX.

1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER

1-3. 额定电流: 1.0A

1-4. 额定电压: 30V

1-5. 耐久性: 10000 CYCLES MIN.

1-6. 耐电压: 100V AC MIN.

1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER

1-8. 绝缘电阻: 100MΩ MIN

1-9. 工作温度: -30° TO +80°


2. 材质:

2.1 胶芯: LCP UL94V-0

2.2 端子: C2680R-H, 镍底, 镀金1μ"

2.3 外壳: SUS201/301, 表面镀雾锡/镀镍

3. 重点尺寸标识"▲"符号

振端精密科技(深圳)有限公司  
Zhenduan precision technology (Shenzhen) Co., LtdTOLERANCE:  
X.XX ±0.30  
X.XXX ±0.20  
X.XXX ±0.10  
X.X ±0.10  
X.X ±0.05  
X.X ±0.05

UNIT: mm [inch]

SCALE: 1:1 SIZE: A4

DRAWN BY:

刘志强

DATE:

2015.08.18

PART NAME:

MC5P母座6.4插板直边

CHECKED BY:

李毅

DATE:

2015.08.18

PART NO.

SEE TABLE

APPROVED BY:

张少辉

DATE:

2015.08.18

DRAW NO:

ZDJNKM000111

SHEET NO.

1 OF 1