



RECOMMENDED P.C.B. LAYOUT (T:1.00mm)  
TOLERANCE UNSPECIFIED ±0.05mm

SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
  - CONTACT RESISTANCE: 30mΩ MAX.
  - DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR ONE MINUTE.
  - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
- MECHANICAL CHARACTERISTICS:
  - INSERTION FORCE :0.5-2.0KgF(REF.)
  - WITHDRAWAL FORCE :0.8-2.0KgF(REF.)
- LIFE TEST: 10,000 CYCLES.
- TO CONFORM TO THE KRCONN HAZARDOUS SUBSTANCE FREE SPEC.

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
6	SHELL	STAINLESS STEEL	NI Plated	1PCS
5	SHIELDING PLATE	STAINLESS STEEL	---	1PCS
4	MD	HIGH TEMPERATURE PLASTIC	BLACK	1PCS
3	CONTACT	COPPER ALLDY	Au/Ni Plated	1SET
2	CONTACT	COPPER ALLDY	Au/Ni Plated	1SET
1	HOUSING	HIGH TEMPERATURE PLASTIC	BLACK	1PCS

A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

**zhenduan 振端精密科技 (深圳) 有限公司**  
Zhenduan precision technology (Shenzhen) Co., Ltd

<b>TOLERANCE:</b> XXX ±0.30 XX ±0.20 X XXX ±0.10 X: ±0.05 X: ±0.02 X: ±0.01	<b>DRAWN BY :</b>	<b>DATE :</b>	<b>PART NAME:</b>	
	刘志强	2015.08.18	TTYPE-C 16P防水立插L10.20	
 UNIT: mm [inch] SCALE: 1:1 SIZE: A4	<b>CHECKED BY:</b>	<b>DATE :</b>	<b>PART NO.</b>	<b>SEE TABLE</b>
	李毅	2015.08.18	<b>MOLD NO.</b>	
<b>APPROVED BY:</b>	<b>DATE :</b>	<b>DRAW NO.:</b>	<b>ZDHS1600FS080</b>	
张少辉	2015.08.18	<b>SHEET NO.</b>	1 OF 1	