



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

备注:

1. 材质:

1.1 胶芯: LCP+30%G.F UL94V-0

1.2 端子: 磷铜, T=0.12mm; 镍底, 镀金1μ”

1.3 外壳: 不锈钢, T=0.30mm; 表面镀镍100μ”
或亮锡100μ”

2. 主要特性:

2.1 额定电流: 0.5A

2.2 接触阻抗: 30mΩ MAX

2.3 绝缘阻抗: 100MΩ MIN 250V DC

2.4 耐压测试: 250V AC

2.5 沾锡性: 温度250±5℃, 时间5±0.5s

2.6 整体插入力: 3.57kgf MAX

整体拔出力: 1.02kgf MIN

2.7 使用寿命: 10000次

2.8 工作温度: -30℃~+80℃

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

深圳市兆达鑫科技有限公司 Shenzhen Zhao Xin Technology Co., Ltd.			
TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.X ±0.05 X.X ±0.025 X.X ±0.015	DRAWN BY : 刘志强	DATE : 2015.08.18	PART NAME: TYPE-C16PIN四脚插板H6.5
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY: 李毅	DATE : 2015.08.18	PART NO. SEE TABLE MOLD NO.
APPROVED BY: 张少辉	DATE : 2015.08.18	DRAW NO.: ZDJNKJ00001601	SHEET NO.: 1 OF 1