



备注:

1.材质:

- 1.1胶芯: LCP+30%G.F UL94V-0
- 1.2端子: 磷铜, T=0.12mm; 镍底, 镀金Xμ”
- 1.3外壳: 不锈钢, T=0.30mm; 表面镀镍100μ”或亮锡100μ”
- 1.4接地片: 不锈钢, T=0.10mm;
- 1.5卡片: 不锈钢, T=0.15mm;

2.主要特性:

- 2.1额定电流: 0.5A
- 2.2接触阻抗: 30mΩ MAX
- 2.3绝缘阻抗: 100MΩ MIN 250V DC
- 2.4耐压测试: 250V AC
- 2.5沾锡性: 温度250±5℃, 时间5±0.5s
- 2.6整体插入力: 3.57kgf MAX
整体拔出力: 1.02kgf MIN
- 2.7使用寿命: 10000次
- 2.8工作温度: -30℃~+80℃

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
IN	SIGNAL NAMF	PIN	SIGNAL NAMF

RECOMMENDED PCB LAYOUT(TOP VIEW)

深圳市兆达鑫科技有限公司 Shenzhen Zhao Xin Technology Co., Ltd.			
TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.X ±0.05 X.X ±0.02 X.X ±0.01	DRAWN BY :	DATE :	PART NAME:
	刘志强	2015.08.18	TYPE-C24P四脚前插后贴H11.95
 UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY:	DATE :	PART NO. SEE TABLE
	李毅	2015.08.18	MOLD NO.
	APPROVED BY:	DATE :	DRAW NO. ZDJNKJ00002422
	张少辉	2015.08.18	SHEET NO. 1 OF 1