



GUIDANCE PLATE	1PCS	PA6	Black	———
Contact	1PCS	Ag	———	———
Shrapnel	1PCS	Beryllium Copper	———	———
Knobe	1PCS	PA66	Gray	———
Cover	1PCS	PA66	Black	———
Base	1PCS	PA66	Black	———
Terminal	3PCS	Brass	Ag Plated	———

1. 额定电压	DC 30V	7. 自由位置 (FP)	9. 80 ± 0.80mm
2. 额定电流	1A	8. 动作位置 (OP)	8. 60 ± 0.80mm
3. 绝缘电阻 (IR)	50兆欧 (Min)	9. 行程 (PT)	1. 20 ± 0.8mm
4. 接触电阻 (CR)	100毫欧 (Max)	10. 机械寿命	20,000次
5. 操作力 (OF)	30 ± 10gf	11. 电气寿命	20,000次
6. 回弹力 (RF)	————	12. 耐压 (WV)	AC250V 1分钟

ZDX 深圳市兆达鑫科技有限公司
Shenzhen Zhao Xin Technology Co., Ltd.

TOLERANCE: X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.XX ±0.10 X.X ±0.10 X ±0.10 X ±0.10 X ±0.10	DRAWN BY:	DATE:	PART NAME:	
	刘志强	2015.08.18	ZD-05数码	
	CHECKED BY:	DATE:	PART NO.	SEE TABLE
李毅	2015.08.18	MOLD NO.	———	
APPROVED BY:	DATE:	DRAW NO.	———	
张少辉	2015.08.18	SHEET NO.	1 OF 1	

UNIT: mm [inch]
SCALE: 1:1 SIZE: A4