



1. Material :
 Contact: Phosphor Bronze
 Insulator: PBT+30%
 G. F. UL 94V-0
 Shell: SPCC
2. Mechanical :
 Mating: 35N max.
 Withdrawal Force: 10N min.
 Durability: 1500 cycles min.
3. Electrical :
 Current-max (amps) 1.5A
 Voltage-max (volts) 30V
 Withstanding Voltage 750V AC
 Contact Resistance (ohms) 30 milliohms max insulation
 Resistance (ohms) 1000 Megohms min.
4. Plating :
 Contacts: Gold And Tin Over
 Nickel Plated
 Shell: Nickel over all plating.
5. Environmental :
 Temperature Range: -55 to 85 .

深圳市兆达鑫科技有限公司 Shenzhen Zhao Xin Technology Co., Ltd.			
TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.XX ±0.10 X.X ±0.05 X.X ±0.05 X.X ±0.05	DRAWN BY : 刘志强	DATE : 2015.08.18	PART NAME: 13.1卷边直脚180度插板
	CHECKED BY : 李毅	DATE : 2015.08.18	PART NO. : SEE TABLE
 UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY : 张少辉	DATE : 2015.08.18	MOLD NO. : DRAW NO. : ZDXAFUSB20002
			SHEET NO. : 1 OF 1