



NOTE:

1. MATERIAL
 - 1.1. HOUSING: HIGH TEMP ;PBT WHITE .
 - 1.2. CONTACT: PHOSPHOR BRONZE T=0.2 .
 - 1.3. SHELL: 铜H62 T=0.30.
2. FINISH:
 - 2.1 CONTACT:1U"AU(MIN),80u"MIN TIN PLATING ON SOLDER TAIL AREA, 50u" MIN. NICKEL UNDERPLATING OVERALL.
 - 2.2 SHELL:1u" AURUM MIN PLATING OVERALL.
3. Electrical Characteristics:

Dielectric Withstanding Voltage:AC 100V At 1 minute,
Insulation Resistance:1000 MΩ/ Min,
Contact Resistance:30mΩ/max.
4. Mechanical Characteristics:

Insertion Force: 35N Maximum.Extraction Force:initial5N-15N Minimum.
After 1500 cycles: 5N-15N Minimum.

ZDX 深圳市兆达鑫科技有限公司
Shenzhen Zhao Xin Technology Co., Ltd.

TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.XX ±0.05 X.X ±0.02 X ±0.01	DRAWN BY : 刘志强	DATE : 2015.08.18	PART NAME: USB AF防水 母座卧式插板L11.6	
	CHECKED BY: 李毅	DATE : 2015.08.18	PART NO.	SEE TABLE
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 张少辉	DATE : 2015.08.18	MOLD NO.	DRAW NO: ZDHS0600FS503
			SHEET NO.	1 OF 1