



RECOMMENDED P. C. B LAYOUT

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000MΩ Min.

Contact Resistance:30 MΩ Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35°C to +85°C

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force:3.5KG MAX

Unmating Force:1.02 KG MIN.

Contact finish:

01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"

04: Selective Gold 15U"

05: Selective Gold 30U"

ZDX 深圳市兆达鑫科技有限公司
Shenzhen Zhao Xin Technology Co., Ltd.

| | | | | |
|--|-------------|------------|-------------|---------------|
| TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.XX ±0.05 X.X ±0.02 X.X ±0.01 | DRAWN BY : | DATE : | PART NAME: | |
| | 刘志强 | 2015.08.18 | 6.8 两脚卷边90度 | |
| UNIT: mm [inch] SCALE:1:1 SIZE: A4 | CHECKED BY: | DATE : | PART NO. | SEE TABLE |
| | 李毅 | 2015.08.18 | MOLD NO. | |
| APPROVED BY: | | DATE : | DRAW NO.: | ZDXAFUSB20053 |
| 张少辉 | | 2015.08.18 | SHEET NO. | 1 OF 1 |