



备注:

1. 产品规格:
  - 1-1. 插入力: 35N MAX.
  - 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER
  - 1-3. 额定电流: 1.0A
  - 1-4. 额定电压: 30V
  - 1-5. 耐久性: 10000 CYCLES MIN.
  - 1-6. 耐电压: 100V AC MIN.
  - 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER
  - 1-8. 绝缘电阻: 100MΩ MIN
  - 1-9. 工作温度: -30° TO +80°
2. 材质:
  - 2.1 胶芯: LCP UL94V-0
  - 2.2 端子: C2680R-H, 镍底, 镀金1μ"
  - 2.3 外壳: SUS201/301, 表面镀雾锡/镀镍
3. 重点尺寸标识"▲"符号

**ZDX** 深圳市兆达鑫科技有限公司  
Shenzhen Zhao Xin Technology Co., Ltd.

TOLERANCE: X X ±0.30 X XX ±0.20 X XXX ±0.10 X . ±0.10 X ° ±10° X ° ±5° X ° ±0.5°	DRAWN BY :	DATE :	PART NAME:	
	刘志强	2015.08.18	MC5P母座全贴板卷边	
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY :	DATE :	PART NO.	SEE TABLE
	李毅	2015.08.18	MOLD NO.	
	APPROVED BY :	DATE :	DRAW NO.:	ZDXMICROM30060
	张少辉	2015.08.18	SHEET NO.	1 OF 1