



PCB寸法

■ 技术参数

- ◆ 额定电压: 250V AC DC
- ◆ 额定电流: 2.0A AC DC
- ◆ 耐压值: 800V AC
- ◆ 绝缘电阻: 800M Ω MIN
- ◆ 接触电阻: 20M Ω MAX
- ◆ 工作温度: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- ◆ 间距: 2.5mm

■ 材料

- ◆ 外壳: 尼龙66
- ◆ 插针: 黄铜

孔数	A	B
2	2.5	7.5
3	5	10
4	7.5	12.5
5	10	15
6	12.5	17.5
7	15	20
8	17.5	22.5
9	20	25
10	22.5	27.5
11	25	30
12	27.5	32.5
13	30	35
14	32.5	37.5
15	35	40
16	37.5	42.5

ZDX 深圳市兆达鑫科技有限公司
Shenzhen Zhao Xin Technology Co., Ltd.

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X.' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 刘志强	DATE : 2016.05.08	PART NAME: 2.5 直针	
	CHECKED BY: 罗秋海	DATE : 2016.05.08	PART NO.	
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 陈鸣杰	DATE : 2016.05.08	MOLD NO.	
			DRAW NO:	
			SHEET NO.	1 OF 1