



- NOTES:
SPECIFICATION:
- 1.CURRENT RATING: 3.0 A
 - 2.VOLTAGE RATING: 3.0 V
 - 3.VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX
SHIELD: 50mΩ/MAX
LLCR MAX. CHANGE OF ALL PINS: 10Ωm
 - 4.INSULATION RESISTANCE: 100MΩ MIN
 - 5.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1MIN
 - 6.INSERTION FORCE: 0.5~2.0kgf
 - 7.UNMATING FORCE: 0.8-2.0kgf
 - 8.DURABILITY: 10000 CYCLES
 - 9.OPERATING TEMPERATURE: -35°C~+85°C
 - 10.THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C
 - 11.WATERPROOF:IP-X8.

USB TYPE C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND

RECOMMEND P.C.B LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

ZDX 深圳市兆达鑫科技有限公司
Shenzhen Zhao Xin Technology Co., Ltd.

TOLERANCE: X.XX ±0.30 X.XXX ±0.20 X.XXX ±0.10 X.X ±10° X.X ±5°	DRAWN BY : 刘志强	DATE : 2015.08.18	PART NAME: TYPE-C16P防水卧式贴板L6.5U型粉末冶金
UNIT: mm [inch] SCALE:1:1 SIZE: A4	CHECKED BY: 李毅	DATE : 2015.08.18	PART NO. SEE TABLE MOLD NO.
	APPROVED BY: 张少辉	DATE : 2015.08.18	DRAW NO: ZDHS0600FS277 SHEET NO. 1 OF 1