



规格说明:Specifications:

电气特性:Electrical:

1. 额定电流: Current Rating  
1.5A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:  
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf (MAX)  
Unmate force: 1.02kgf (MIN)
2. 端子保持力: Terminal Retention  
1.2kgf (MIN)

原材料: Material:

1. 塑胶: Housing:  
High Temperature Thermoplastics,  
UL 94V-0 PBT White/Black
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;  
Tin On Solder Tails
2. 外壳: Shell:  
Nickel Plating

变更说明: 1. 耳朵上的孔, 由直径1.7改为2.0mm  
2. 耳朵往尾部方向加胶, 增厚, 平USB座子尾端  
3. 尾部加2个定位柱, 大小和位置可变动, 按贵司模具上的方便为准

<b>振端精密科技(深圳)有限公司</b> Zhenduan precision technology (Shenzhen) Co., Ltd			
TOLERANCE: X:XX ±0.30 X:XXX ±0.20 X:XXX ±0.10 X:° ±10° X:° ±5°	DRAWN BY : 刘志强	DATE : 2015.08.18	PART NAME: USB AF防水 母座180度H10.8有耳
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY: 李毅	DATE : 2015.08.18	PART NO.: SEE TABLE
	APPROVED BY: 张少辉	DATE : 2015.08.18	DRAW NO.: ZDHS0600FS501
			SHEET NO.: 1 OF 1