

RECOMMENDED P.C.B LAYOUT

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000MΩ Min.

Contact Resistance:30 MΩ Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35℃ to +85℃

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force:3.5KG MAX

Unmating Force:1.02 KG MIN.

Contact finish:

01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"


04: Selective Gold 15U"

05: Selective Gold 30U"



振端精密科技(深圳)有限公司
Zhenduan precision technology (Shenzhen) Co., Ltd

TOLERANCE:	±0.30
X.XX	±0.20
X.XXX	±0.10
X.X	±0.10
X.X	±0.10
X.X	±0.10
X.X	±0.10
X.X	±0.10



UNIT: mm [inch]
SCALE: 1:1 SIZE: A4

DRAWN BY:	DATE:	PART NAME:
刘志强	2015.08.18	6.3 两脚直边90度 山字型
CHECKED BY:	DATE:	PART NO.
李毅	2015.08.18	SEE TABLE
APPROVED BY:	DATE:	MOLD NO.
张少辉	2015.08.18	
		DRAW NO:
		ZDXAFUSB20023
		SHEET NO.
		1 OF 1