



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A1251-02A	1.25	4.25
A1251-03A	2.50	5.50
A1251-04A	3.75	6.75
A1251-05A	5.00	8.00
A1251-06A	6.25	9.25
A1251-07A	7.50	10.50
A1251-08A	8.75	11.75
A1251-09A	10.00	13.00
A1251-10A	11.25	14.25
A1251-11A	12.50	15.50
A1251-12A	13.75	16.75
A1251-20A	23.75	26.75

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	A1251-NA		版本 REV.	A
			X.±0.25	X.*±2'	审核	2013、07、01	张名	品名 TITLE	1.25开口直针 WAFER DIP TYPE		页次 SHEET	1/1
			.X±0.20	.X'±1'	核准	2013、07、03	张名	客户料号 CUTM. NO.				
			.XX±0.15	.XX'±0.5'	APPROVAL	2013、07、05	张名	振端精密科技（深圳）有限公司 Zhenduan precision technology (Shenzhen) Co., Ltd				
			.XXX±0.10	.XXX'±0.5'	单位 UNITS	MM	比例 SCALE	1:1				