



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A1251-02AW	1.25	4.25
A1251-03AW	2.50	5.50
A1251-04AW	3.75	6.75
A1251-05AW	5.00	8.00
A1251-06AW	6.25	9.25
A1251-07AW	7.50	10.50
A1251-08AW	8.75	11.75
A1251-09AW	10.00	13.00
A1251-10AW	11.25	14.25
A1251-11AW	12.50	15.50
A1251-12AW	13.75	16.75
A1251-20AW	23.75	26.75

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生			料号 PART NO.	A1251-NAW		版本 REV.	A		
			X.±0.25	X.*±2'		审核 CHECK	2013、07、01			1.25开口弯针				页次 SHEET	1/1
			.X±0.20	.X*±1'			2013、07、03			WAFER DIP TYPE					
			.XX±0.15	.XX*±0.5'		核准 APPROVAL	2013、07、05			客户料号 CUTM. NO.					
.XXX±0.10	.XXX*±0.5'	单位 UNITS	MM	比例 SCALE	1:1		<b>振端精密科技（深圳）有限公司</b> Zhenduan precision technology (Shenzhen) Co., Ltd								