


SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated
Solder tad Brass Tin-plated



编 号	尺寸 (mm)	
	A	B
A1251WF-02A	1.25	7.35
A1251WF-03A	2.50	8.60
A1251WF-04A	3.75	9.85
A1251WF-05A	5.00	11.10
A1251WF-06A	6.25	12.35
A1251WF-07A	7.50	13.60
A1251WF-08A	8.75	14.85
A1251WF-09A	10.00	16.10
A1251WF-10A	11.25	17.35
A1251WF-11A	12.50	18.60
A1251WF-12A	13.75	19.85
A1251WF-20A	23.75	29.85

PCB LAYOUT

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	A1251WF-NA		版本 REV.	A
			X.±0.25	X.±2°		2013、07、01		品名	1.25贴片		页次	1/1
			.X±0.20	.X±1°	审核	2013、07、03	张名	TITLE	WAFER SMT TYPE		SHEET	
			.XX±0.15	.XX±0.5°	核准		张名	客户料号 CUTM. NO.				
			.XXX±0.10	.XXX±0.5°	APPROVAL	2013、07、05		振端精密科技（深圳）有限公司 Zhenduan precision technology (Shenzhen) Co., Ltd				
					单位 UNITS	MM	比例 SCALE	1:1				