



PCB寸法

■ 技术参数

- ◆ 额定电压: 250V AC DC
- ◆ 额定电流: 2.0A AC DC
- ◆ 耐压值: 800V AC
- ◆ 绝缘电阻: 800M Ω MIN
- ◆ 接触电阻: 20M Ω MAX
- ◆ 工作温度: -25℃~+85℃
- ◆ 间距: 2.5mm

■ 材料

- ◆ 外壳: 尼龙66
- ◆ 插针: 黄铜

孔数	A	B
2	2.5	7.5
3	5	10
4	7.5	12.5
5	10	15
6	12.5	17.5
7	15	20
8	17.5	22.5
9	20	25
10	22.5	27.5
11	25	30
12	27.5	32.5
13	30	35
14	32.5	37.5
15	35	40
16	37.5	42.5

振端精密科技 (深圳) 有限公司
Zhenduan precision technology (Shenzhen) Co., Ltd

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5' UNIT: mm [inch] SCALE:1:1 SIZE: A4	DRAWN BY :	DATE :	PART NAME:	
	刘志强	2016.05.08	2.5 直针	
	CHECKED BY:	DATE :	PART NO.	
	罗秋海	2016.05.08	MOLD NO.	
	APPROVED BY:	DATE :	DRAW NO:	
	陈鸣杰	2016.05.08	SHEET NO.	1 OF 1