



Recommnd PCB Layout

Poles	Part No	Dimensions (mm)	
		A	B
2		2.50	7.50
3		5.00	10.00
4		7.50	12.50
5		10.00	15.00
6		12.50	17.50
7		15.00	20.00
8		17.50	22.50
9		20.00	25.00
10		22.50	27.50
11		25.00	30.00
12		27.50	32.50
13		30.00	35.00
14		32.50	37.50
15		35.00	40.00
16		37.50	42.50
17		40.00	45.00
18		42.50	47.50
19		45.00	50.00
20		47.50	52.50

**■ SPECIFICATIONS**

- Voltage rating: 250V AC, DC
- Current rating: 3A, AC, DC
- Withstanding Voltage: 1000V AC/minute
- Insulation resistance: 1000MΩmin
- Temperature range: -25° C~+85° C
- Contact resistance: Intial value/10mΩmax
- After envionmental testing/20mΩmax

**■ WAFER**

- Part No.: 8823S-XX
- Poles: 02-20
- Material: Nylon 66 UL 94V-0
- Q'ty: 1000 pcs/bag

**振端精密科技 (深圳) 有限公司**  
Zhenduan precision technology (Shenzhen) Co., Ltd

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 刘志强	DATE : 2016.05.08	PART NAME: 2.5 90° 弯针	
	CHECKED BY: 罗秋海	DATE : 2016.05.08	PART NO.	
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY: 陈鸣杰	DATE : 2016.05.08	MOLD NO.	
			DRAW NO:	
			SHEET NO.	1 OF 1