



P. C. B LAYOUT

主要技术性  
 间距: 1.5mm  
 温度范围: -25~+85℃  
 额定电压: 50V AC, DC  
 额定电流: 0.5A AC, DC  
 接触阻抗: 0.04Ω  
 绝缘阻抗: 800MΩ  
 耐压: 200V AC/minute

材料  
 壳体: LCP  
 UL 94V-0 本色  
 接触针: 黄铜 (镀锡)  
 焊片: 磷青铜 (镀锡)

NO. of Contacts (n)	Dimensions		
	A	B	C
002	1.5	2.9	6.1
003	3.0	4.4	7.6
004	4.5	5.9	9.1
005	6.0	7.4	10.6
006	7.5	8.9	12.1
007	9.0	10.4	13.6
008	10.5	11.9	15.1
009	12.0	13.4	16.6
010	13.5	14.9	18.1
011	15.0	16.4	19.6
012	16.5	17.9	21.1
013	18.0	19.4	22.6
014	19.5	20.9	24.1
015	21.0	22.4	25.6
016	22.5	23.9	27.1
017	24.0	25.4	28.6
018	25.5	26.9	30.1
019	27.0	28.4	31.6
020	28.5	29.9	33.1

**ZHENDUAN** 振端精密科技 (深圳) 有限公司  
 Zhenduan precision technology (Shenzhen) Co., Ltd

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 刘志强	DATE : 2016.05.08	PART NAME: 1.5 卧式贴片Wafer	
	CHECKED BY: 罗秋海	DATE : 2016.05.08	PART NO.	
	APPROVED BY: 陈鸣杰	DATE : 2016.05.08	MOLD NO.	
	UNIT: mm [inch] SCALE:1:1 SIZE: A4		DRAW NO:	
			SHEET NO.	1 OF 1